

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
1 July 2004 (01.07.2004)

PCT

(10) International Publication Number
WO 2004/055919 A2

(51) International Patent Classification⁷: **H01L 51/20**

Devin, John [US/US]; 404 Portofino DR #4, San Carlos CA 94020 (US).

(21) International Application Number:
PCT/GB2003/005430

(74) Agents: EVANS, Marc, Nigel et al.; Page White & Farrer, 54 Doughty Street, London WC1N 2LS (GB).

(22) International Filing Date:
12 December 2003 (12.12.2003)

(81) Designated States (*national*): AE, AG, AI, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0229191.2 14 December 2002 (14.12.2002) GB

(71) Applicant (*for all designated States except US*): **PLASTIC LOGIC LIMITED** [GB/GB]; 34 Cambridge Science Park, Milton Road, Cambridge CB4 0FX (GB).

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **BROWN, Thomas** [GB/GB]; 26 Willow Walk, Cambridge CB1 1LA (GB). **SIRRINGHAUS, Henning** [DE/GB]; 73 Whitwell Way, Coton, Cambridge CB3 7PW (GB). **MACKENZIE,**


(84) Designated States (*regional*): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report

[Continued on next page]

(54) Title: ELECTRONIC DEVICES



(57) Abstract: A method for forming an electronic device having a multilayer structure, comprising: embossing a surface of a substrate so as to depress first and second regions of the substrate relative to at least a third region of the substrate; depositing conductive or semiconductive material from solution onto the first and second regions of the substrate so as to form a first electrode on the first region and a second electrode on the second region, wherein the electrodes are electrically insulated from each other by the third region.

BEST AVAILABLE COPY

WO 2004/055919 A2